



DECLARATION OF PERFORMANCE
No. 025.00

1. Name and code of the product:

Product: MAXFLEX 900

Batch: See packaging

2. Name and contact address of the manufacturer or importer or distributor:

Name: DRIZORO, SAU

Contact address: C/Primavera 50-52. P. Ind. Las Monjas. 28850-Torrejón de Ardoz. (Madrid, Spain)

3. Intended use:

TWO-COMPONENT POLYSULPHIDE-BASED ELASTOMERIC JOINT SEALANT WITH HIGH CHEMICAL RESISTANCE FOR PERMANENT IMMERSION APPLICATIONS

4. System of assessment and verification of constancy of performance: System 4

5. Declared performance

Essential Characteristics	Performance	Harmonised Technical Specification
System	Two components (M)	EN 14188-2:2005
Type	NS	
Class	Class A, B, C	
Polymer Base	Polysulfide	
Adherence		
Tensile modulus at -20 ° C (MPa)	0,38	
Failure of adhesion / cohesion	None	
Cohesion		
Tensile modulus at +23°C	0,25	
Failure of adhesion / cohesion	None	
Tensile modulus at -20 ° C (MPa)	0,36	
Failure of adhesion / cohesion	None	
Cohesion in cold climates		
Tensile modulus at -30 ° C (MPa)	0,50	
Failure of adhesion / cohesion	None	
Elastic recovery (%)	83	
Volume loss (%)	-3	
Sealing durability against chemicals		
Mass change (%)	-8	
Volume change (%)	+15	
Cohesion durability against chemicals		
Failure of adhesion / cohesion	None	
Durability of all mandated characteristics against aging		
Variation of tensile modulus (%)	8	
Failure of adhesion / cohesion	None	

Registro Mercantil de Madrid, Tomo 5.027, Libro 4.181, Sección 3ª, Folio 1, Hoja 39.745, N.I.F.: ESA 28498038

- The performance of the product identified in point 1 is in conformity with the declared performance in point 5.
- This declaration of performance is issued under the sole responsibility of the manufacturer, importer or distributor identified in point 2.
- Signed for and behalf of the manufacturer, or importer or distributor by:



Mr. Francisco Rodríguez Álvarez.
Director of Quality and Environment.

Torrejón de Ardoz, 27th March, 2015