

DECLARATION OF PERFORMANCE
No. 142.01



1. Name and code of the product:

Product: MAXSHEEN ELASTIC

Batch: See packaging

2. Name and contact address of the manufacturer or importer or distributor:

Name: DRIZORO, SAU

Contact address: C/Primavera 50-52. P. Ind. Las Monjas. 28850-Torrejón de Ardoz. (Madrid, Spain)

3. Intended use:

ACRYLIC COATING FOR SURFACE PROTECTION OF CONCRETE according to EN 1504-9
 PROTECTION AGAINST INGRESS (1.3), MOISTURE CONTROL (2.2), AND INCREASING
 RESISTIVITY (8.2).

4. System of assessment and verification of constancy of performance: System 2+

5. Notified body:

Name and identification number: AENOR, 0099

Notified task: Assessment of the Factory Production Control

System of assessment: System 2+

Certificate of the Factory Production Control: 0099/CPR/B15/0010

6. Declared performance

Essential Characteristics	Performance	Harmonised Technical Specification
PERMEABILITY TO CO ₂	S _D ≥ 50 m	EN 1504-2:2004
WATER VAPOUR PERMEABILITY	Class I: S _D < 5 m	EN 1504-2:2004
CAPILLARY ABSORPTION AND PERMEABILITY TO WATER	0,006 kg·m ⁻² ·h ^{-0.5}	EN 1504-2:2004
ADHESION	≥ 1,0 N/mm ²	EN 1504-2:2004
ADHESION AFTER THERMAL COMPATIBILITY Freeze salt cycling with de-icing immersion	≥ 0,8 N/mm ²	EN 1504-2:2004
CRACK BRIDGING ABILITY Static / Dynamic	A1 (-30°C) / B1 (-30°C)	EN 1504-2:2004
ARTIFICIAL WEATHERING (UV-radiation and humidity)	Pass	EN 1504-2:2004
REACTION TO FIRE	NPD	EN 1504-2:2004
DANGEROUS SUBSTANCES	Comply 5.3	EN 1504-2:2004

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued under the sole responsibility of the manufacturer, importer or distributor identified in point 2.
- Signed for and behalf of the manufacturer, or importer or distributor by:



Mr. Francisco Rodríguez Álvarez
 Director of Quality and Environment.

Torrejón de Ardoz, 4th January 2017